

# Enhanced Water Removal from PEM Fuel Cell Flow Channels by Superimposing Acoustic Wave



Dr. Mehdi Mortazavi



Dr. Anthony D. Santamaria



Dr. Jingru Z. Benner



Dr. Vedang Chauhan

Department of Mechanical Engineering  
Western New England University  
Springfield, MA

4<sup>th</sup> Thermal and Fluids Engineering Conference  
American Society of Thermal and Fluid Engineers  
Las Vegas, NV

April 14-17, 2019

# What is a Fuel Cell?

Fuel cell is an energy conversion device that converts chemical energy into electrical energy.

- Electrochemical reaction, no chemical reaction
- High operating efficiency
- No moving parts
- Quick refuel

## Proton Exchange Membrane (PEM) Fuel Cell

- Low temperature fuel cell ( $30^{\circ} - 100^{\circ}\text{C}$ )
- Hydrogen is used as fuel, air (oxygen) is used as oxidizer
- Anode:  $H_2 \longrightarrow 2H^+ + 2e^-$
- Cathode:  $\frac{1}{2}O_2 + 2H^+ + 2e^- \longrightarrow H_2O$


The water produced in the cathode of a PEM fuel cell:

- May hydrate the membrane
  - May be *passively* removed (back diffusion to anode, corner flow, evaporation, and etc.)
  - May fill open pores of GDL
  - May clog the flow channels
- } are referred to as **flooding**

**Flooding** is reported to deteriorate the performance of the cell and should be avoided.


- In this study, water removal from an ex-situ PEM fuel cell flow channel is investigated with an *active* approach.

# Experimental Setup




# Experimental Conditions


- Flow channel size 3 mm (W)  $\times$  2.4 mm (H)
- Air flow rate 788 ml/min (superficial velocity 1.82 m/s)
- Air Reynolds number 319.2
- Water flow rate 400, 600, and 800  $\mu\text{l}/\text{h}$  (superficial velocity  $9.25 \times 10^{-4}$ ,  $1.38 \times 10^{-3}$ ,  $1.82 \times 10^{-3}$  m/s)
- Water Reynolds number 2.76, 4.14, 5.52
- Frequencies applied 20 to 120 Hz with a 20-Hz interval (sine wave)
- Superimposition methods: (i) continuous, (ii) pulsating on and off (10 s), and (iii) *on demand*



# Results, Flow Channel Images






# Results, Cumulative Water Area






$$\text{cumulative area at time } t = \sum_{i=1}^t \text{area of water droplet in image at time } t$$


# Results cont., Cumulative Water Area






# Results cont., Pressure Drop



# Results cont., Pressure Drop



# Results cont., *on Demand*



Reference:

Mehdi Mortazavi, Anthony D. Santamaria, Jingru Z. Benner, and Vedang Chauha, *Enhanced Water Removal from PEM Fuel Cells Using Acoustic Pressure Waves*, Journal of The Electrochemical Society, 166 (7) F1-F11 (2019)

Thank you!

Thank you!